

Flat LIGHTLINE®

LFHF-203

Description

Flat LIGHTLINE is a rectangular composite developed as a non-metallic strength element for fiber cables. Flat LIGHTLINE is a highly flexible, all dielectric composite for crossply sheathing and ballistic protection for fiber optic cables and is an effective non-metallic strength element for fiber and copper cables, which provides excellent mechanical protection against impact, crush, abrasion, and rodent protection.

Typical LFH LIGHTLINE Physical Properties

Fiber Type	E-Glass
Resin Type	Epoxy
Approximate Fiber Percentage, by weight	80%
Approximate Resin Percentage, by weight	20%
Coefficient of Thermal Expansion (CTE)	$5.9 \times 10^{-6} \text{ C}^\circ$

Typical Flat LFH LIGHTLINE Mechanical Properties

Tensile Strength	> 1.24 GPa
Modulus of Elasticity	> 50 GPa
Flexural Modulus	> 48 GPa
Elongation at Break	> 2.5%

Flat LFH LIGHTLINE Standard Sizes

Product	Metric	Inches
LFHF-203	2.03 x 0.76mm ± 0.08	0.080 x 0.030" ± 0.003

NEPTCO warrants that its products will work in a manner consistent with the capabilities described in the data sheet. NEPTCO reserves the right to improve, enhance, and modify the features and specifications of these products. This warranty shall be void if the product has been tampered with or improperly used. Except for the express warranty and limited remedies described above, NEPTCO disclaims all other warranties including implied warranties. NEPTCO and its authorized agents shall have no other liability beyond the price of the product for damages to a purchaser, including consequential damages, occurring in connection with the use or performance of the product.

