

MULETAPE®

It's All About Pull,
Power & Performance

Whether you're installing cable or locating your underground network, NEPTCO MULETAPE has the power and performance you need. Available in a variety of constructions including woven polyester and aramid, versatile MULETAPE allows you to thread, measure, pull and detect with a single product, saving both time and money.

- Prelubricated for easy pulling and reduced friction
- Available in strengths from 200 to 6,000 lbs. (91-2727 kg) for greater pulling capacity and durability
- Durably printed with sequential footage or metric markings
- Packaged in splice-free lengths up to 100,000 ft. (30 km) for faster, easier cable placement
- Low elongation enhances worker safety and prevents crushed capstans
- Lightweight, easily blown through conduit or innerduct
- Detectable MULETAPE contains an insulated metallic conductor for easy cable and duct location

Contact NEPTCO today and harness the power of MULETAPE.



Visit us on line at:
www.muletape.com

Polyester MULETAPE®

Product #	Strength (lbs/kg)	Typical Bowline Strength (lbs/kg)	Typical MULEKNOT Strength (lbs/kg)	Minimum Reel Lengths (ft/km)	Maximum Reel Lengths (ft/km)	Approximate Width
WP200N*	200/91	110/50	150/68	3000/1	100,000/31	1/8"
WP400P	400/182	190/86	300/136	3000/1	100,000/31	1/4"
WP600P	600/273	360/164	468/213	3000/1	100,000/31	3/8"
WP900P	900/409	480/218	770/350	3000/1	100,000/31	1/2"
WP1250P	1250/568	760/345	900/409	3000/1	70,000/21	1/2"
WP1800P	1800/818	830/377	1400/636	3000/1	50,000/15	5/8"
RP1800P	1800/818	830/377	1400/636	3000/1	50,000/15	3/8"
WP2500P	2500/1136	1300/591	1800/818	3000/1	25,000/8	3/4"
RP3300P	3300/1500	1900/864	2900/1318	1000/0.3	3,000/1	1/2"
RP4000P	4000/1818	2300/1045	3500/1591	1000/0.3	3,000/1	5/8"
RP6000P	6000/2727	3080/1400	5000/2273	1000/0.3	3,000/1	3/4"

*Product is only available unprinted.

Detectable Polyester MULETAPE® – 22-gage and 24-gage conductors

22 Gage Product #	24 Gage Product #	Strength (lbs/kg)	Typical Bowline Strength (lbs/kg)	Typical MULEKNOT Strength (lbs/kg)	Minimum Reel Lengths (ft/km)	Approximate Width
DT400P	DP400P	400/182	190/86	300/136	3000/1	1/4"
DT900P	DP900P	900/409	480/218	770/350	3000/1	1/2"
DT1250P	DP1250P	1250/568	760/345	900/409	3000/1	1/2"
DT1800P	DP1800P	1800/818	830/377	1400/636	3000/1	5/8"
DT2500P	DP2500P	2500/1136	1300/591	1800/818	3000/1	3/4"

QUADTAPE® Detectable MULETAPE® – Patented design featuring four individual 22-gage conductors

Product #	Strength (lbs/kg)	Minimum Reel Lengths (ft/km)	Approximate Width
DT1250P/4P	1250/568	3000/1	9/16"

Aramid MULETAPE®

Product #	Strength (lbs/kg)	Minimum Reel Lengths (ft/km)	Approximate Width
WL1250	1250/567	3000/1	1/4"
WL1500	1500/680	3000/1	1/4"
WL1800	1800/816	3000/1	3/8"
WL 2000	2000/907	3000/1	3/8"
WL 2500	2500/1134	3000/1	1/2"

1. All products are available unprinted.
2. All printed products are also available with meter markings.

